

7kg Matapouri



Stain Resistance



Suitable for stairs.



Antistatic



High Stitch Rating



Fade Resistance



High Twist Rating

Product Name	7kg Matapouri
Construction	Hard Twist Cut Pile
Yarn	100% Solution Dyed Nylon
Width	3.66m
Yarn Specification	2 Ply BCF
Gauge	1/10 th Gauge
Yarn weight	55oz
Total Height	14.5mm
Secondary backing	Synthetic Jute
Anti-allergenic	Resistant to mould & mildew
Electrical properties	Antistatic
Warranty	15 Years Warranty
Rating	Extra Heavy Duty Residential (Stairs)

Green Label Plus Certification

All of our carpets are Green Label Plus® certified, the highest indoor air quality standard for carpet products. This certification ensures extremely low VOC (volatile organic compound) emissions, helping to create healthier indoor environments by reducing airborne pollutants. This is especially important in New Zealand homes and buildings, which are often well-insulated and tightly sealed for energy efficiency. Green Label Plus certified carpets support better air quality, safer living and working spaces, and align with New Zealand's growing focus on sustainable, environmentally responsible building practices.



Specifications & Installation Notes

- Must be installed in accordance with AS/NZS 2455.1
- Seam sealer is required on all joins
- Chair mats or protective pads are recommended under chairs with castors to maintain appearance retention
- Pile reversal, shading or watermarking may occur in cut pile carpets and is a natural characteristic, not a manufacturing defect
- Colour, shade and specification variations may occur within normal manufacturing tolerances
- Samples may vary from the final product supplied
- Specifications and materials may change without notice without affecting product performance

*The technical details and other information contained in this document are given in good faith and represent product data we believe to be accurate at the time of printing. Technical details are based on averages obtained from the manufacturing process which may vary within normal industry tolerances.