

Berberpoint 920

Construction	Structured Needlepunch Carpet
Yarn	100% Stainproof Miracle Fibre
Width	4.2m
Standard Roll Length	35m
Total Weight	1107g/m ²
Total Thickness	7.0mm
Backing	Resinbac
Electrical Properties	Antistatic
Electrical Propensity	<2.0kV (DIN66095 Part 4)
Fire Rating	CRF 2.2kW/m ² (ISO 9239-1)
VOC Rating	Pass (GLP Criteria)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. It is recommended that the carpet be adhered directly to the subfloor, which should be clean, dry and level. All adjacent pieces must be laid running in the same direction. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified Product Health Declaration™ Low VOC, solution dyeing uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ± 3 mm, Pile Weight $\pm 5\%$.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex[®]

**A World of
Perfect Choices** ■