

# Emotions



<b>Construction</b>	Heterogeneous Sheet Vinyl
<b>Width</b>	2.0m (no selvage edge)
<b>Standard Roll Length</b>	20m
<b>Pattern Repeat</b>	Random repeat, reverse laying
<b>Total Weight</b>	3100g/m <sup>2</sup>
<b>Wear Layer Thickness</b>	0.7mm
<b>Total Thickness</b>	2.0mm
<b>Surface Protection</b>	Protecsol®
<b>Slip Resistance</b>	R10 (AS 4586:2013, App D)
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	≤ 2kV (EN 1815)
<b>Fire Rating</b>	CRF 8.7kW/m <sup>2</sup> (ISO 9239-1)
<b>Wear Resistance</b>	≤2mm <sup>3</sup> (EN 660.2)
<b>Wear Group</b>	T (EN 649)
<b>Type Binder Content</b>	I (EN ISO 10582)
<b>Dimensional Stability</b>	≤0.40% ISO 23999, EN 434
<b>Thermal Conductivity</b>	0.25W/mK (EN ISO 10456, EN 12524)
<b>Indoor Air Quality</b>	TVOC after 28 days <100µg/m <sup>3</sup> (ISO 16000-6) FloorScore®
<b>Underfloor Heating</b>	Suitable up to 27°C
<b>Residual Indentation</b>	≤ 0.1mm (EN ISO 24343-1, EN 433)
<b>Colour Fastness</b>	≥6 (EN ISO 105 - B02)
<b>Chemical Resistance</b>	Good ISO 26987, EN 423
<b>Classification</b>	Class 34 Commercial Very Heavy Class 43 Industrial Heavy
<b>Warranties</b>	10 Year Commercial Warranty
<b>Installation</b>	Random Repeat, Reverse Sheet for Seaming Cove Fillet or Pencil Cove is recommended on all installations. Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	100% Recyclable REACH Compliant Environmental Management ISO 14001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances.
- This product is intended for use solely as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.
- Rubber Migration: Rubber migration (also known as Plasticiser Migration) is a condition that can cause vinyl to discolour. It is caused by rubber or latex products, eg rubber or latex-soled slippers, shoes and rubber backed mats, coming to contact with the vinyl over a constant period of time. It is neither a manufacturing nor an installation fault and therefore is not covered by our warranties.
- Plain, granite or patterned vinyls will either need to be reverse laid or a wider width should be used to allow for colour inequality, an additional allowance may have to be made for the pattern repeat.

# Belgotex®

## A World of Perfect Choices