

Precinct™

Technical Data

Product Classification

| | | |
|--------------------------------|-------------------------------------|--------------------------------|
| Type of floor covering | | Multi-Level Loop Carpet Tile |
| Yarn type | | Solution Dyed Nylon |
| ACCS Classification (Use Area) | Commercial | Commercial Heavy Duty & Stairs |
| Warranty* | Commercial - available upon request | 15 years |

*All warranties are in addition to any rights consumers may have under Australian and New Zealand consumer laws. Terms and conditions apply - for full information in respect to the scope of the commercial warranty, contact your Armstrong Flooring representative.

Physical Properties

| | | |
|----------------------------|-----------|--------------------------------------|
| Colours (Standard) | - | 6 |
| Dimensions | ISO 24342 | 500mm x 500mm |
| Gauge | - | 1/12th |
| Pile weight | - | 575g/m ² (± 25.0g) / 17oz |
| Overall thickness | - | 5.8mm (± 1.0mm) |
| Pile height | - | 3.0mm (± 0.5mm) |
| Backing | - | HP Bac |
| Stain resistance treatment | - | Yes |
| Tiles/carton | - | 20 |
| m ² /carton | - | 5.0 |
| m ² /pallet | - | 180.0 |
| kg/carton | - | 15.0 |

Installation

| | | |
|--|---|-------------------------|
| | To current AS/NZS 2455.1 & AS2455.2 (latest versions) and Armstrong Flooring Installation Instructions - Carpet Tiles | 1/4 Turn, Ashlar, Brick |
|--|---|-------------------------|

Sustainability

| | | |
|------------------------|---|---|
| Backing minimisation | - | PVC & Bitumen Free |
| Carpet & Rug Institute | - | CRI Green Label + Plus |
| TVOC emissions | - | Compliant with Green Building Council low emitting VOC emission rates |

Technical Performance

| | | |
|------------------------------|--|--------------------------------------|
| Fire resistance | AS ISO 9239-1 Critical Radiant Flux (CHF Value) Smoke Development Rate | ≥ 4.5kW/m ² ≤ 750%.min |
| Colour fastness | ISO 105-B02, Method 3 | ≥ 6 |
| Dimensional stability | ISO 23999 | ≤ 0.2% |
| Castor chair | ISO 4918 | Pass |
| Static electrical propensity | ISO 6356/AATCC 134 | Antistatic ≤ 2.5kV |

Accreditation

Manufactured under accredited ISO 9001 quality, ISO 14001 environmental and ISO 45001 OHS management systems

All specifications are current as at date of publication and may be changed without notice. For current and complete specifications please visit armstrongflooring.au or armstrongflooring.co.nz
All Armstrong Flooring products must be installed in accordance with the relevant Australian and/or New Zealand applicable standards and the Armstrong Flooring Installation Instructions.
Variations may occur between samples, photographic images, and batches in terms of colour, shade, pattern or similar.

AU: www.armstrongflooring.au/precinct

NZ: www.armstrongflooring.co.nz/precinct

Armstrong Flooring and the Armstrong Flooring logo are under license from AWI Licensing, LLC

ArmstrongFlooring™