

# Prevail



<b>Construction</b>	Scroll Loop Pile Carpet Tile
<b>Yarn</b>	100% Solution Dyed Nylon
<b>Size</b>	500mm x 500mm
<b>Tiles per Carton</b>	20pcs / 5.0m <sup>2</sup>
<b>Pile Weight</b>	550g/m <sup>2</sup>
<b>Total Weight</b>	4525g/m <sup>2</sup>
<b>Pile Height</b>	2.5mm
<b>Total Thickness</b>	5.5mm
<b>Machine Gauge</b>	1/10th
<b>Backing</b>	PVC
<b>Electrical Properties</b>	Antistatic
<b>Electrical Propensity</b>	0.2kV (ISO 6356)
<b>Fire Rating</b>	CRF 6.8kW/m <sup>2</sup> (AS ISO9239-1)
<b>VOC Rating</b>	<0.5 mg/m <sup>2</sup> /hour (ASTM D5116-06)
<b>Anti-allergenic Properties</b>	Will not shed or pill. Resistant to mould & mildew.
<b>Underfloor Heating</b>	Suitable
<b>Colour Fastness</b>	5/5 on Grey Scale (ISO105-B02)
<b>Rating</b>	Heavy Duty Commercial
<b>Stair Rating</b>	Suitable
<b>Warranties</b>	15 Year Commercial Warranty
<b>Installation</b>	Laying recommendation: Quarter Turn or Brick Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
<b>Environmental</b>	CRI Green Label Certified Low VOC, Solution dyeing uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Toitu Carbonreduce Organisation Certified ISO 14064-1



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

# Belgotex®

## A World of Perfect Choices