

Seastride



Construction	Tufted Textured Loop Pile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m ²
Pile Weight	545g/m ²
Total Weight	3080g/m ²
Pile Height	3.5mm
Total Thickness	5.8mm
Machine Gauge	1/12th
Primary Backing	100% PET Non-woven
Backing	PVC
Electrical Properties	Antistatic
Fire Rating	CRF 4.7kW/m ² (ISO 9239-1)
VOC Rating	<0.5mg/m ² /h – Green Label Plus (ASTM D5116-06)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Colour Fastness to Light	6-7 (ISO 105-B02)
Colour Fastness to Rubbing	Wet 4-5 (AS/NZS 2111.19.1) Dry 4-5 (AS/NZS 2111.19.1)
Thermal Resistance	Suitable
Stair Rating	Suitable
Warranties	10 Year Commercial Warranty
Installation	Laying recommendation: Quarter Turn or Brick Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	CRI Green Label Certified, Low VOC Solution dyeing uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Occupational Health and Safety Management ISO 45001



- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices