

BPIR Data Sheet

Duratap

1/2

Product class

Class 1 - Batch or mass-produced products

Product name

Duratap - Entry Carpet System

Place Manufactured (New Zealand or Overseas)

The Netherlands

Product description and its intended use

Duratap is a 17mm thick 100% natural coconut fibre entry carpet bonded to a unique backing with integrated stability scrim. Maximum roll size 2.0 x 20meters Duratap has a stiff, bristle feel with the natural touch of coir fibre and has natural variation in colour and density.

Relevant Building Code clauses

B2

Durability

—
Performance clause B2.3.1 c) 5 years

C3

Fire Affecting Area beyond the source

—
Performance clause C3.4 b) - does not apply to detached dwellings, within household units in multiunit dwellings or outbuildings and ancillary buildings.

D1

Access Routes

—
Performance clause D1.3.3 d)

F2

Hazardous Building Materials

—
Performance clause F2.3.1

Statement of how the building product is expected to contribute to compliance

B2

Durability

B2.3.1 c)

—
Duratap entry carpet has a durability beyond 5 years, based on NZBC B2/VM1 clause 1.1 In-service history.

—
Durability supported by a 2 year product warranty.

C3

Fire Affecting Area beyond the source

C3.4 b)

—
Duratap has been tested to AS ISO 9239.1 - 2003 and achieves a CHF (Critical Heat Flux) mean of 6.4kW/m². Refer to AWTA Product Testing, Test Report 15.01948.02, dated 18.05.2015.

D1

Access Routes

D1.3.3 d)

—
Duratap entry mat meets the requirements for slip resistance in accordance with NZBC D1/AS1 2.1 Slip Resistance, Table 2 Slip Resistance for walking surface. Duratap is acceptable for level and sloping surfaces, wet and dry slip resistance.

F2

Hazardous Building Materials

F2.3.1

—
Duratap is manufactured from non-toxic materials.

We are here to help you, if you have any questions or require further clarification please contact us.

BPIR Data Sheet

Duratap

2/2

Limitations on the use of the building product

- Duratap entrance mats are not suitable for exterior, weather exposed applications. Suitable for interior or weather protected areas only.

Design requirements that would support the appropriate use of the building product

- NA

Installation requirements

- Install in accordance with Advance Flooring, Installation Instructions - Duratap.
- Recommended to be installed with an Advance Flooring matwell surround frame.
- After frame installation, prepare substrate base to suit depth of matting and to provide a smooth, level base.
- For ease of maintenance loose lay installation is recommended.

Maintenance requirements

- Maintenance to be in accordance with Advance Flooring, Maintenance Instructions - Advance Entry Carpet.
- Daily maintenance - soiling removed with vacuum cleaner. Chewing gum to be removed as soon as it appears by use of specialist products.